

SC400N1-L HDV対応解像度一覧

ビデオ/S	解像度	24	25	30	50	55	56	59.9	60		70	72	75	85	備考
	720x240								○						
	720x288				○										
	720x480i							○							
	720x576i				○										

※ビデオ/Sはキャプチャー後は30pで処理されます。

HDMI	解像度	24	25	30	50	55	56	59.9	60		70	72	75	85	備考
	720x480							○	○						
	720x576				○										
	1280x720				○			○	○						
	1920x1080i				○			○	○						

コネクタ/D端子 (Y,Cb,Cr)	解像度	24	25	30	50	55	56	59.9	60		70	72	75	85	備考
	720x240								○						
	720x288				○										
	720x480i							○							
	720x576i				○										
	720x480							○							
	720x576				○										
	1280x720				○			○							
	1920x1080i				○			○							
	1920x1080				○			○							

PC/GAME (RGB/DVI)	解像度	24	25	30	50	55	56	59.9	60	67	70	72	75	85	備考
	720x240								○						
	720x288				○										
	720x480i							○							
	720x576i				○										
	640 x 350													○	
	640 x 384								○						
	640 x 400 PC9801						○								
	640 x 400 PC9821(DMT)										○				
	640 x 400								○					○	
	720 x 400										×				
	640 x 480								○	○		○	○	○	
	720 x 480							○	○						
	768 x 512					○									
	848 x 480								○						
	720 x 576				○										
	800x600						○		○			○	○	○	
	832x624												○		
	1024x600								○						
	1024x768								○		○		○	○	
	1280x720				○				○				○	○	
	1280x768								○				○	○	
	1280x960								○				○	○	
	1360x768								○						
	1366x768								○						
	1280x800								○						
	1152x864								○				○		
	1152x870												○		
	1440x900								○				○	○	
	1600x900								○						
	1280x1024								○				○	○	
	1400x1050								○				○		
	1650x1050								○						
	1920x1080				○				○						
	1600x1200								○						
	1920x1200								○						
		24	25	30	50	55	56	59.9	60	67	70	72	75	85	

※電気的な違いによりTTLデジタルRGB信号には対応しません。

※X68000の15kHzは映らない場合があります。インターレース映像は対応できません。

※アナログRGB信号では似通った解像度、似通った周波数の場合はあやまって他の解像度情報を使用して表示してしまう場合があります。

※同じ解像度でも機種や機器、同じ機器でも表示モードによってピクセルクロック（ドットクロック）やピクセル比が異なるため、画質が低下したりモアレが発生する場合があります。

参考：  水色のマス目はアナログのみ対応を示します。